COUNTY OF ROCKLAND

Department of General Services Purchasing Division

Contract Award Notification

Title: Potassium Permanganate

Contract Period: June 1, 2024, through November 30, 2024, w/ (4) six-month options

Original Date of Issue: July 2, 2024

Date of Revision:

BID No: 5918BPS WC (RFB-WC-24139)

Catalog: Wastewater

Authorized Users: County Agencies

Address Inquiries To:

Name: Michele Phillips Title: Purchaser I Phone: 845-364-2984 Fax: 845-364-3809

E-mail: phillipm@co.rockland.ny.us

Description

This contract is for moving services.

| Contract # | Vendor Number | Contractor & Address | Telephone No. |
|------------|---------------|-----------------------|---------------|
| 5918BPS WC | 0000022227 | Chemrite, Inc. | 770-271-5576 |
| | | 5202 Belle Wood Court | |
| | | Buford, GA 30518 | |
| | | Contact: Aaron Opp & | |
| | | Kimberly Miller | |
| | | orders@chemrite.com | |

PAGE 1 OF 13

County of Rockland CONTRACT

Contract ID

5918BPS WC

Contract Dates

Freight Terms

Buyer

06/01/2024 to 11/30/2024

Potassium Permanganate

PHILLIPS, MICHELE

Dept. of General Services
Purchasing Division
50 Sanatorium Rd
Bldg A, 6th Fl, Room 609
POMONA NY 10970
MANUAL TOPPUR 10970
MA www.rcpurchasing.com

> Supplier 06 Chemrite, Inc. 0000022227 Aaron Opp 5202 Belle Wood Court Suite 104 Buford GA 30518

Phone 770/271-5576 Fax 770/271-4068 sales@chemrite.com

| Line # Supplier Item | Item Desc | Item ID | Price | UOM |
|----------------------|---|-------------|-----------|------|
| 1 | Potassium Permanganate (Chemrite) K-Ox, oxident, 330 lb steel drum, (\$1.939 per lb). FOB destination. Pricing as per Westchester contract 5918BPS. 4 drums per skid. Must order by skid qty. | 88540540002 | 641.20800 | Drum |

TERMS AND CONDITIONS OF 5918BPS WC (RFB-WC-24139) INCORPORATED HEREIN BY REFERENCE.

Authorized Signature

Paul J Breun

Dispatch via Print

Contract Maximum

70,000.00

Fax

845/364-3809

Currency

USD

phillipm@co.rockland.ny.us

Buyer Email

845/364-2984

Phone

Page

1 of 1



Department of Finance

Bureau of Purchase & Supplies 148 Martine Avenue, Room 713 White Plains, NY 10601 (914) 231-1872 www.westchestergov.com

CONTRACT AWARD NOTIFICATION

| TITLE: | Potassium Permanganate | |
|----------------------------------|---|-------------------------|
| CONTRACT NUMBER: | 5918-BPS | (Replaces #5868bps) |
| CONTRACT PERIOD: | June 01, 2024 through November 30, 2024 | |
| DATE OF ISSUE: | May 22, 2024 | |
| NEW EXTENDED CONTRACT PERIOD: | | |
| COUNTY DEPARTMENTS: | DEF, Participating | Municipalities |
| SPECIFICATION REFRENCE: | As Incorporated In | The Invitation for Bids |
| CONTRACTOR INFORMATION: | Appears on the attached pages of this Award | |

Address Inquiries To:

| County Departments & Vendors | Political Subdivisions |
|---|--------------------------|
| Name: Valsala Panicker Title: Buyer Phone: 914-231-1329 Fax: 914-231-1546 E-mail: mmcf@Westchestergov.com | Customer Service SAME |

Description

A Contract has been established for Potassium Permanganate, effective June 01, 2024 through November 30, 2024, for use by the Westchester County Department of Environmental Facilities and all Political Subdivisions of Westchester County.



A Contract has been established for Potassium Permanganate, effective June 01, 2024 through November 30, 2024, for use by the Westchester County Department of Environmental Facilities and all Political Subdivisions of Westchester County. Prices are shown below.

Vendor:

728674

Chemrite, Inc.

5202 Bell Wood Court

Suite 104

Buford, GA 30518, Attn: Aaron Opp.

Telephone Number: 770-271-5576

E-mail: orders@chemrite.com

Terms: Net 30

FOB: Destination

Delivery: 7 days ARO

Potassium Permanganate delivered pricing:

55 lb. (approx.) drums

\$106.867 per drum

(Primary Supplier)

Price per lb. for 55 lb. drum

\$1.939 per lb.

330 lb. (approx.) drums

\$641.208 per drum

(Primary Supplier)

Price per lb. for 330 lb. drum

\$1.939per lb.

(Primary Supplier)

3,000 lb. (approx.) totes Price per lb. for 3,000 lb. bin \$8,550.00

\$2.85 per lb.

Ordering department must check invoice prices and quantities delivered against each invoice.

Westchester County Departments make Payments by entering GAX document referencing Contract number 5918BPS and sending the signed GAX with the invoice to Finance – Accounts Payable, Room 728, 148 Martine Avenue, White Plains, NY 10601.

SAFETY DATA SHEET

1. Identification

Product identifier K-Ox, Potassium Permanganate

Other means of identification

SDS number -

Recommended use Potassium Permanganate is an oxidant recommended for applications that require a strong

oxidant.

Recommended restrictionsUse in accordance with supplier's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company name Chemrite, Inc.

Address 5202 Belle Wood Ct., Ste 104

Buford, GA 30518 USA

Telephone 877-248-0017
E-mail info@chemrite.com
Website www.chemrite.com

Emergency Telephone For Hazardous Materials [or Dangerous Goods] Incidents ONLY

(spill, leak, fire, exposure or accident), call CHEMTREC at

CHEMTREC®, USA: 001 (800) 424-9300 CHEMTREC®, Canada: 001 (703) 527-3887

2. Hazard(s) identification

Physical hazardsOxidizing solidsCategory 2Health hazardsAcute toxicity, oralCategory 4Skin corrosion/irritationCategory 1B

Serious eye damage/eye irritation Category 1

Specific target organ toxicity, single exposure Category 1 (Respiratory System)

Specific target organ toxicity, repeated Category 1 (Respiratory System)

exposure

Category 1 (Respiratory System, Central Nervous System)

Hazardous to the aquatic environment, acute

hazard

Hazardous to the aquatic environment, Category 1

long-term hazard

OSHA defined hazards Not classified.

Label elements

Environmental hazards



Signal word Danger

Hazard statement May intensify fire; oxidizer. Harmful if swallowed. Causes severe skin burns and eye damage.

Causes damage to organs (Respiratory System). Causes damage to organs (Respiratory System, Central Nervous System) through prolonged or repeated exposure. Very toxic to aquatic life with

Category 1

long lasting effects.

Precautionary statement

Prevention Keep away from heat. Keep/Store away from clothing and other combustible materials. Take any

precaution to avoid mixing with combustibles. Do not breathe dust. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Do not eat,

drink or smoke when using this product. Avoid release to the environment.

K-Ox potassium permanganate SDS US

Revision date: 10/10/2017 Issue date: 10/10/2017

Response

In case of fire: Use water for extinction. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor. If exposed: Call a poison center/doctor. Collect spillage.

Storage

Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

3. Composition/information on ingredients

Substances

| Chemical name | Common name and synonyms | CAS number | % |
|------------------------|--------------------------|------------|--------|
| Potassium permanganate | Synonyms | 7722-64-7 | > 97.5 |

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. For breathing difficulties, oxygen may be necessary. Get medical attention immediately.

Skin contact

Take off immediately all contaminated clothing. Immediately flush skin with plenty of water. Get medical attention immediately. Wash contaminated clothing before reuse.

Contact with skin may leave a brown stain of insoluble manganese dioxide. This can be easily removed by washing with a mixture of equal volume of household vinegar and 3% hydrogen peroxide, followed by washing with soap and water.

Eye contact

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open

eyelids wide apart. Continue rinsing. Get medical attention immediately.

Ingestion

Immediately rinse mouth and drink plenty of water. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention immediately.

Most important symptoms/effects, acute and delayed

Contact with this material will cause burns to the skin, eyes and mucous membranes. Permanent eye damage including blindness could result.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Decomposition products are alkaline. Brown stain is insoluble manganese dioxide.

General information

In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. For personal protection, see Section 8 of the SDS. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Flood with water from a distance, water spray or fog.

The following extinguishing media are ineffective: Dry chemical. Foam. Carbon dioxide (CO2). Halogenated materials.

Specific hazards arising from the chemical

May intensify fire; oxidizer. May ignite combustibles (wood, paper, oil, clothing, etc.). Contact with incompatible materials or heat (135 °C / 275 °F) could result in violent exothermic chemical reaction. Oxidizing agent, may cause spontaneous ignition of combustible materials. By heating and fire, corrosive vapors/gases may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.

Fire-fighting equipment/instructions

Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Dike fire control water for later disposal. Water runoff can cause environmental damage.

General fire hazards

The product is not flammable. May intensify fire; oxidizer. May ignite combustibles (wood, paper, oil, clothing, etc.). Contact with incompatible materials or heat (135 °C / 275 °F) could result in violent exothermic chemical reaction.

K-Ox potassium permanganate SDS US

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Methods and materials for containment and cleaning up

Keep unnecessary personnel away. Keep upwind. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors and contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Local authorities should be advised if significant spillages cannot be contained.

Keep combustibles (wood, paper, oil, etc.) away from spilled material. Should not be released into the environment. This product is miscible in water. Stop leak if possible without any risk. Dike the spilled material, where this is possible. Clean up spills immediately by sweeping or shoveling up the material. Do not return spilled material to the original container; transfer to a clean metal or plastic drum. To clean up potassium permanganate solutions, follow either of the following two options:

Option # 1: Dilute to approximately 6% with water, and then reduce with sodium thiosulfate, a bisulfite or ferrous salt solution. The bisulfite or ferrous salt may require some dilute sulfuric acid (10% w/w) to promote reduction. Neutralize with sodium carbonate to neutral pH, if acid was used. Decant or filter and deposit sludge in approved landfill. Where permitted, the sludge may be drained into sewer with large quantities of water.

Option # 2: Absorb with inert media like diatomaceous earth or inert floor dry, collect into a drum and dispose of properly. Do not use saw dust or other incompatible media. Disposal of all materials shall be in full and strict compliance with all federal, state, and local regulations pertaining to permanganates.

To clean contaminated floors, flush with abundant quantities of water into sewer, if permitted by federal, state, and local regulations. If not, collect water and treat as described above.

Environmental precautions

Never return spills in original containers for re-use. For waste disposal, see Section 13 of the SDS. Do not allow to enter drains, sewers or watercourses. Contact local authorities in case of spillage to drain/aquatic environment.

7. Handling and storage

Precautions for safe handling

Take any precaution to avoid mixing with combustibles. Do not get this material in your eyes, on your skin, or on your clothing. Do not breathe dust or mist or vapor of the solution. Use personal protection as recommended in Section 8 of the SDS. If clothing becomes contaminated, remove and wash off immediately. When using, do not eat, drink or smoke. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Avoid release to the environment.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep container tightly closed and in a well-ventilated place. Store in a cool, dry place. Store away from incompatible materials (See Section 10). Store in accordance with NFPA 430 requirements for Class II oxidizers.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Туре | Value | |
|--|---------|---------|--|
| Potassium permanganate (CAS 7722-64-7) | Ceiling | 5 mg/m3 | |

US. ACGIH Threshold Limit Values

| Material | Туре | Value | Form |
|--|------------------|--------------------|----------------------|
| K-Ox Potassium Permanganate | TWA | 0.1 mg/m3 | Inhalable fraction. |
| | | 0.02 mg/m3 | Respirable fraction. |
| | _ | | F |
| Components | Туре | Value | Form |
| Potassium permanganate (CAS 7722-64-7) | T ype TWA | Value 0.1 mg/m3 | Inhalable fraction. |

US. NIOSH: Pocket Guide to Chemical Hazards

| Material | Туре | Value | Form | |
|--|--|----------------------|-------|--|
| K-Ox Potassium Permanganate | TWA | 1 mg/m3 | Fume. | |
| Components | Туре | Value | Form | |
| Potassium permanganate (CAS 7722-64-7) | STEL | 3 mg/m3 | Fume. | |
| , | TWA | 1 mg/m3 | Fume. | |
| ological limit values | No biological exposure limits noted fo | r the ingredient(s). | | |

K-Ox potassium permanganate SDS US

Revision date: 10/10/2017 Issue date: 10/10/2017

Exposure guidelines Follow standard monitoring procedures.

Appropriate engineering

controls

Provide adequate general and local exhaust ventilation. An eye wash and safety shower must be

available in the immediate work area.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Wear face shield if there is risk of splashes.

Skin protection

Hand protection Wear chemical-resistant, impervious gloves. Use protective gloves made of: Rubber or plastic.

Suitable gloves can be recommended by the glove supplier.

Other Wear appropriate chemical resistant clothing. Rubber or plastic apron.

Respiratory protection

In case of inadequate ventilation or risk of inhalation of dust, use suitable respiratory equipment with particle filter. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134.

Measurement Element: Manganese (Mn) 10 ma/m3

Any particulate respirator equipped with an N95, R95, or P95 filter (including N95, R95, and P95 filtering face pieces) except quarter-mask respirators. The following filters may also be used: N99,

R99, P99, N100, R100 or P100. Any supplied-air respirator.

25 mg/m3

Any supplied-air respirator operated in a continuous-flow mode.

Any powered, air-purifying respirator with a high-efficiency particulate filter.

50 mg/m3

Any air-purifying, full-face piece respirator equipped with an N100, R100, or P100 filter.

Any supplied-air respirator with a tight-fitting face piece that is operated in a continuous-flow mode. Any powered, air-purifying respirator with a tight-fitting face piece and a high-efficiency particulate

Any self-contained breathing apparatus with a full face piece.

Any supplied-air respirator with a full face piece.

Any supplied-air respirator operated in a pressure-demand or other positive-pressure mode.

Emergency or planned entry into unknown concentrations or IDLH conditions -Any self-contained breathing apparatus that has a full face piece and is operated in a pressure-demand or other positive-pressure mode.

Any air-purifying, full-face piece respirator equipped with an N100, R100, or P100 filter.

Any appropriate escape-type, self-contained breathing apparatus.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Keep from contact with clothing and other combustible materials. Remove and wash contaminated clothing promptly. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and

safety practice.

9. Physical and chemical properties

Dark purple solid with metallic luster. **Appearance**

Solid. Physical state Solid. Form Color Dark purple. Odor Odorless. Not available. Odor threshold Not applicable.

Melting point/freezing point Starts to decompose with evolution of oxygen (O2) at temperatures above 150 °C. Once

initiated, the decomposition is exothermic and self-sustaining.

Initial boiling point and boiling

range

pН

Not applicable.

Not applicable. Flash point **Evaporation rate** Not applicable. Flammability (solid, gas) Non flammable. Upper/lower flammability or explosive limits

Flammability limit - lower Not applicable.

(%)

K-Ox potassium permanganate SDS US Flammability limit - upper

(%)

Not applicable.

Explosive limit - lower (%)

Not available. **Explosive limit - upper (%)** Not available.

Vapor pressure

< 0 kPa at 25 °C Not

applicable.

Vapor density

Not applicable.

2.7 (20 °C) (Water = 1)

Relative density Solubility(ies)

6 % (20 °C) Solubility (water) Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available. **Decomposition temperature** 464 °F (240 °C) **Viscosity** Not applicable.

Other information

Density 2.70 g/cm3

Not explosive. Can explode in contact with sulfuric acid, peroxides and metal powders. **Explosive properties**

H-Mn-O4.K Molecular formula 158.03 g/mol Molecular weight 158.03

Strong oxidizing agent. **Oxidizing properties**

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Stable at normal conditions. Chemical stability

Possibility of hazardous

reactions

Contact with combustible material may cause fire. Can explode in contact with sulfuric acid. peroxides and metal powders. Starts to decompose with evolution of oxygen (O2) at temperatures

above 150 °C. Once initiated, the decomposition is exothermic and self-sustaining.

Conditions to avoid Contact with incompatible materials or heat (135 °C / 275 °F) could result in violent exothermic

chemical reaction.

Acids. Peroxides. Reducing agents. Combustible material. Metal powders. Contact with Incompatible materials

hydrochloric acid liberates chlorine gas.

Hazardous decomposition

products

By heating and fire, corrosive vapors/gases may be formed.

11. Toxicological information

Information on likely routes of exposure

Harmful if swallowed. Ingestion

Inhalation May cause irritation to the respiratory system.

Skin contact Causes severe skin burns. Eye contact Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics Contact with this material will cause burns to the skin, eyes and mucous membranes. Permanent

eye damage including blindness could result.

Information on toxicological effects

Harmful if swallowed. Acute toxicity

Components **Species Test Results**

Potassium permanganate (CAS 7722-64-7)

Acute

Dermal

LD50 Rat 2000 mg/kg

Oral

LD50 Rat 2000 mg/kg

Skin corrosion/irritation Causes severe skin burns. Serious eye damage/eye Causes serious eye damage.

irritation

K-Ox potassium permanganate SDS US Respiratory or skin sensitization

Not classified. Respiratory sensitization Not classified. Skin sensitization Not classified. Germ cell mutagenicity Not classified. Carcinogenicity Not classified. Reproductive toxicity

Specific target organ toxicity -

single exposure

Causes damage to organs (respiratory system).

Specific target organ toxicity repeated exposure

Causes damage to organs (respiratory system, central nervous system) through prolonged or

repeated exposure.

Not classified. **Aspiration hazard**

Chronic effects May cause damage to respiratory system. Prolonged exposure, usually over many years, to

manganese oxide fume/dust can lead to chronic manganese poisoning, chiefly affecting the

central nervous system.

12. Ecological information

Ecotoxicity Very toxic to aquatic life with long lasting effects.

| Components | | Species | Test Results |
|----------------------------|----------------|---|-----------------------------------|
| Potassium permanganate (C | CAS 7722-64-7) | | |
| Aquatic | | | |
| Fish | LC50 | Bluegill (Lepomis macrochirus) | 2.7 mg/l, 96 hours, static |
| | | | 2.3 mg/l, 96 hours, flow through |
| | | | 2.3 mg/l, 96 hours |
| | | | 1.8 - 5.6 mg/l |
| | | Carp (Cyprinus carpio) | 3.16 - 3.77 mg/l, 96 hours |
| | | | 2.97 - 3.11 mg/l, 96 hours |
| | | Goldfish (Carassius auratus) | 3.3 - 3.93 mg/l, 96 hours, static |
| | | Milkfish, salmon-herring (Chanos chanos) | > 1.4 mg/l, 96 hours |
| | | Rainbow trout (Oncorhynchus mykiss) | 1.8 mg/l, 96 hours |
| | | | 1.08 - 1.38 mg/l, 96 hours |
| | | | 0.77 - 1.27 mg/l, 96 hours |
| | | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 0.275 - 0.339 mg/l, 96 hours |
| cictones and degradability | Expected to k | se readily converted by oxidizable material | ls to insoluble manganese oxide |

Persistence and degradability **Bioaccumulative potential**

Expected to be readily converted by oxidizable materials to insoluble manganese oxide.

Potential to bioaccumulate is low.

Mobility in soil The product is miscible with water. May spread in water systems.

Other adverse effects None known.

13. Disposal considerations

Disposal instructions Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazardous waste code D001: Ignitable waste

The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Do not allow this material to drain into sewers/water supplies.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Rinse container at least three times to an absence of pink color before disposing. Empty

containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number UN1490

UN proper shipping name

Potassium permanganate

Transport hazard class(es) Class

5.1 Subsidiary risk Ш **Packing group**

K-Ox potassium permanganate

Revision date: 10/10/2017 Issue date: 10/10/2017

Environmental hazards

Marine pollutant Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IB8, IP2, IP4, T3, TP33 **Special provisions**

Packaging exceptions 152 212 Packaging non bulk 240 Packaging bulk

IATA

UN1490 **UN** number

UN proper shipping name Potassium permanganate

Transport hazard class(es)

Class 5.1 Subsidiary risk 5.1 Label(s) **Packing group** Ш **Environmental hazards** Yes **ERG Code** 5L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1490

POTASSIUM PERMANGANATE **UN proper shipping name**

Transport hazard class(es)

Class 5.1 Subsidiary risk Label(s) 5.1 **Packing group** Ш **Environmental hazards**

Marine pollutant Yes F-H. S-Q **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

Drug Enforcement Administration (DEA) (21 CFR 1310.02 (b) 8: List II chemical.

Department of Homeland Security (DHS) Chemical Facility Anti-Terrorism Standards (6 CFR 27,

Appendix A): Listed.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

CERCLA Hazardous Substance List (40 CFR 302.4)

Potassium permanganate (CAS 7722-64-7) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Chemical name CAS number % by wt. 7722-64-7 Potassium permanganate > 97.5

K-Ox potassium permanganate SDS US

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Potassium permanganate (CAS 7722-64-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Clean Water Act (CWA) Section 112(r) (40 CFR Hazardous substance

68.130)

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Potassium permanganate (CAS 7722-64-7) 6579

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Potassium permanganate (CAS 7722-64-7) 15 % wt

DEA Exempt Chemical Mixtures Code Number

Potassium permanganate (CAS 7722-64-7) 6579

US state regulationsThis product does not contain a chemical known to the State of California to cause cancer, birth

defects or other reproductive harm.

California OSH Hazardous Substance List: Listed.

US. Massachusetts RTK - Substance List

Potassium permanganate (CAS 7722-64-7)

US. New Jersey Worker and Community Right-to-Know Act

Potassium permanganate (CAS 7722-64-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Inventory name

Potassium permanganate (CAS 7722-64-7)

US. Rhode Island RTK

Potassium permanganate (CAS 7722-64-7)

US. California Proposition 65

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Not listed.

International Inventories

Country(s) or region

| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
|-------------|--|-----|
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | Yes |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date 27-November-2013

 Revision date
 10/10/17

 Version #
 02

United States & Puerto Rico

Further information HMIS® is a registered trade and service mark of the NPCA.

K-Ox potassium permanganate SDS US

Yes

On inventory (yes/no)*

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

NFPA Ratings



List of abbreviations

GHS: Globally Harmonized System of Classification and Labeling of hazardous properties of

Chemicals.

TWA: Time weighted average. LD50: Lethal Dose, 50%.

LC50: Lethal Concentration, 50%.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association.

MARPOL: International Convention for the Prevention of Pollution from Ships.

References HSDB® - Hazardous Substances Data Bank

Registry of Toxic Effects of Chemical Substances (RTECS) IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

DisclaimerThe information contained herein is accurate to the best of our knowledge. However, data, safety

standards and government regulations are subject to change and, therefore, holders and users should satisfy themselves that they are aware of all current data and regulations relevant to their particular use of product. CHEMRITE, INC DISCLAIMS ALL LIABILITY FOR RELIANCE ON THE COMPLETENESS OR ACCURACY OR THE INFORMATION INCLUDED HEREIN. CHEMRITE, INC MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTIES OF MERCHANTIABILITY OR FITNESS FOR PARTICULAR USE OR

PURPOSE OF THE PRODUCT DESCRIBED HEREIN. All conditions

relating to storage, handling, and use of the product are beyond the control of Chemrite, Inc, and

shall be the sole responsibility of the holder or user of the product.

This SDS contains revisions in the following section(s):

This safety data sheet contains revisions in the following section(s):

K-Ox potassium permanganate SDS US