COUNTY OF ROCKLAND
Department of General Services
Purchasing Division

Contract Award Notification

Title:	**Potassium Permanganate (Cairox)**
Contract Period:	June 1, 2025, through November 30, 2025, w/ (4) six-month options **Ext. through May 31, 2026, w/ (3) six-month options**
Original Date of Issue:	May 23, 2025
Date of Revision:	10/27/25
BID No:	**5970BPS WC (RFB-WC-25073)**
Catalog:	**Wastewater**
Authorized Users:	United States Agencies, Other States & Political Subdivisions Therein, Local Governments, School Districts & Non-Profit Agencies

Address Inquiries To:

Name: Michele Phillips
Title: Purchaser II
Phone: 845-364-2984
Fax: 845-364-3809
E-mail: phillipm@co.rockland.ny.us

Description
This contract is to provide Potassium Permanganate

Contract #	Vendor Number	Contractor & Address	Telephone No.
5970BPS WC	0000027617	Carus, LLC 315 Fifth Street Peru, IL 61534 Contact: Barbie Smith bids@carusllc.com	800-435-6856 815-224-6697

County of Rockland
CONTRACT

Dept. of General Services
Purchasing Division
50 Sanatorium Rd, Bldg A, 6th Fl, Rm 609
Inside Delivery - No Loading Dock
POMONA NY 10970
www.rcpurchasing.com

Dispatch via Print

Contract ID		Page 1 of 1
5970BPS WC		
Contract Dates	**Currency**	
06/01/2025 to 05/31/2026	USD	
	Contract Maximum	
Potassium Permanganate Cairox	75,000.00	
Freight Terms	**Buyer Email**	
	phillipm@co.rockland.ny.us	
Buyer	**Phone**	**Fax**
PHILLIPS, MICHELE	845/364-2984	845/364-3809

Supplier 0000027617
Carus LLC
Barbie Smith
315 Fifth St.
Peru IL 61354

Phone 800/435-6856

bids@carusllc.com

Tax Exempt? Tax Exempt ID:

Line #	Supplier Item	Item Desc	Item ID	Price	UOM
1		POTASSIUM PERMANGANATE - CAIROX, (CAS number 7722-64-7) 330.75 lb Steel drum, ($1.70 per lb) FOB destination, 4 drums per palette, must order by palette, minimum 4 drums. Pricing as per Westchester contract 5970-BPS	88540540001	562.28000	Drum

TERMS AND CONDITIONS OF 5970BPS WC INCORPORATED HEREIN BY REFERENCE.

Authorized Signature

Department of Finance

Bureau of Purchase & Supplies
148 Martine Avenue, Room 713
White Plains, NY 10601
(914) 231-1872
www.westchestergov.com

CONTRACT AWARD NOTIFICATION

TITLE:	**Potassium Permanganate**
CONTRACT NUMBER:	**5970-BPS** (Replaces #5949 & 5950bps)
CONTRACT PERIOD:	June 01, 2025 through November 30, 2025
DATE OF ISSUE: **1st Extension – Issue Date**	May 05, 2025 **September 30, 2025**
1ST EXTENSION PERIOD:	**December 01, 2025 through May 31, 2026**
COUNTY DEPARTMENTS:	DEF, Participating Municipalities
SPECIFICATION REFRENCE:	As Incorporated In The Invitation for Bids
CONTRACTOR INFORMATION:	Appears on the attached pages of this Award

Address Inquiries To:

County Departments & Vendors	Political Subdivisions
Name : Valsala Panicker Title : Buyer Phone : 914-231-1329 Fax : 914-231-1546 E-mail: mmcf@Westchestergov.com	Customer Service SAME

Description

A Contract has been extended for Potassium Permanganate, effective December 01, 2025 through May 31, 2026, for use by the Westchester County Department of Environmental Facilities and all Political Subdivisions of Westchester County.

A Contract has been established for Potassium Permanganate, effective December 01, 2025 through May 31, 2026, for use by the Westchester County Department of Environmental Facilities and all Political Subdivisions of Westchester County. Prices are shown below.

Vendor: 985271 W
Carus Corporation
315 Fifth Avenue
Peru, IL 61354
Telephone Number (800)435-6856

Terms: Net 30

FOB: Destination

Delivery: 7 days ARO

Potassium Permanganate delivered pricing:

55 lb. (approx.) drums	**$93.71 (for 55.125 lb. drum/pail)**	**(Primary**
Price per lb. for 55.125 lb. drum	**$1.70 per lb.**	**Supplier)**
330 lb. (approx.) drums	**$562.28 (for 330.75 lb. drum)**	**(")**
Price per lb. for 330.75 lb. drum	**$1.70 per lb.**	
3,300 lb. Carus Cycle Bin	**$10,650.15 (for 3,307.5 lb. cycle bin**	**("**
Price per lb. for 3,307.5 lb. bin	**$3.22 per lb.**	

Ordering department must check invoice prices and quantities delivered against each invoice.

Westchester County Departments make Payments by entering GAX document referencing Contract number 5970BPS and sending the signed GAX with the invoice to Finance – Accounts Payable, Room 728, 148 Martine Avenue, White Plains, NY 10601.

SAFETY DATA SHEET

1. Identification

Product identifier **CAIROX® potassium permanganate**

Other means of identification

SDS number -

CAS number 7722-64-7

Recommended use CAIROX® potassium permanganate is an oxidant recommended for applications that require a strong oxidant.

Recommended restrictions Use in accordance with supplier's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company name CARUS LLC

Address 315 Fifth Street,
Peru, IL 61354, USA

Telephone +1 815 223-1500 - All other non-emergency inquiries about the product should be directed to the company

E-mail salesmkt@carusllc.com

Website www.carusllc.com

Contact person Sr. Manager Global Corporate Product Stewardship, RCMS Coordinator

Emergency Telephone For Hazardous Materials [or Dangerous Goods] Incidents ONLY
(spill, leak, fire, exposure or accident), call CHEMTREC at
CHEMTREC®, USA: 001 (800) 424-9300
CHEMTREC®, Mexico (Toll-Free - must be dialed from within country): 01-800-681-9531
CHEMTREC®, Other countries: 001 (703) 527-3887

2. Hazard(s) identification

Physical hazards	Oxidizing solids	Category 2
Health hazards	Acute toxicity, oral	Category 4
	Skin corrosion/irritation	Category 1C
	Serious eye damage/eye irritation	Category 1
	Reproductive toxicity (the unborn child)	Category 2
	Specific target organ toxicity, repeated exposure (inhalation)	Category 2 (Brain)
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 1
	Hazardous to the aquatic environment, long-term hazard	Category 1

OSHA defined hazards Not classified.

Label elements

Signal word Danger

Hazard statement May intensify fire; oxidizer. Harmful if swallowed. Causes severe skin burns and eye damage. Suspected of damaging the unborn child. May cause damage to organs (Brain) through prolonged or repeated exposure by inhalation. Very toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep/Store away from clothing//combustible materials. Take any precaution to avoid mixing with combustibles/. Keep away from heat. Do not breathe dust. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Avoid release to the environment.
Response	In case of fire: Use appropriate media for extinction. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor/. Wash contaminated clothing before reuse. Collect spillage.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Substances

Chemical name	Common name and synonyms	CAS number	%
Potassium permanganate		7722-64-7	>97

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. For breathing difficulties, oxygen may be necessary. Get medical attention immediately.

Skin contact Take off immediately all contaminated clothing. Immediately flush with plenty of water for at least 15 minutes. Call a physician or poison control center immediately. Wash contaminated clothing before reuse. Chemical burns must be treated by a physician.

Contact with skin may leave a brown stain of insoluble manganese dioxide. This can be easily removed by washing with a mixture of equal volume of household vinegar and 3% hydrogen peroxide, followed by washing with soap and water.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Ingestion Immediately rinse mouth and drink plenty of water. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention immediately.

Most important symptoms/effects, acute and delayed Contact with this material will cause burns to the skin, eyes and mucous membranes. Permanent eye damage including blindness could result.

Indication of immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Decomposition products are alkaline. Brown stain is insoluble manganese dioxide.

General information In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. For personal protection, see Section 8 of the SDS. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Flood with water from a distance, water spray or fog.

Unsuitable extinguishing media The following extinguishing media are ineffective: Dry chemical. Foam. Carbon dioxide (CO2). Halogenated materials.

Specific hazards arising from the chemical May intensify fire; oxidizer. May ignite combustibles (wood, paper, oil, clothing, etc.). Contact with incompatible materials or heat (135 ºC / 275 ºF) could result in violent exothermic chemical reaction. Oxidizing agent, may cause spontaneous ignition of combustible materials. By heating and fire, corrosive vapors/gases may be formed. During fire, gases hazardous to health may be formed such as: Manganese oxides. Potassium oxides. Formic acid

Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Dike fire control water for later disposal. Water runoff can cause environmental damage.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	The product is not flammable. May intensify fire; oxidizer. May ignite combustibles (wood, paper, oil, clothing, etc.). Contact with incompatible materials or heat (135 °C / 275 °F) could result in violent exothermic chemical reaction.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Do not get in eyes, on skin, on clothing. Do not breathe dust. Minimize dust generation and accumulation. Keep upwind. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Wear protective clothing as described in Section 8 of this safety data sheet. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	Keep combustibles (wood, paper, oil, etc.) away from spilled material. Should not be released into the environment. This product is miscible in water. Stop leak if possible without any risk. Dike the spilled material, where this is possible. Clean up spills immediately by sweeping or shoveling up the material. Do not return spilled material to the original container; transfer to a clean metal or plastic drum. To clean up potassium permanganate solutions follow the following recommendation: Absorb with inert media like diatomaceous earth or inert floor dry, collect into a drum and dispose of properly. Do not use saw dust or other incompatible media. Disposal of all materials shall be in full and strict compliance with all federal, state, and local regulations pertaining to permanganates. To clean contaminated floors, flush with abundant quantities of water into sewer, if permitted by federal, state, and local regulations. If not, collect water and treat as described above. Never return spills in original containers for re-use. For waste disposal, see Section 13 of the SDS. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.
Environmental precautions	Do not allow to enter drains, sewers or watercourses. Contact local authorities in case of spillage to drain/aquatic environment.

7. Handling and storage

Precautions for safe handling	Take any precaution to avoid mixing with combustibles. Do not get this material in your eyes, on your skin, or on your clothing. Do not breathe dust or mist or vapor of the solution. If clothing becomes contaminated, remove and wash off immediately. When using, do not eat, drink or smoke. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Avoid release to the environment. Wear appropriate personal protective equipment (See Section 8). Wash contaminated clothing before reuse.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep container tightly closed and in a well-ventilated place. Store in a cool, dry place. Store in accordance with NFPA 400 Hazardous Materials Code requirements. Store away from incompatible materials (See Section 10).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Additional components	Type	Value	Form
Manganese compounds (potassium permanganate). (CAS 7439-96-5)	Ceiling	5 mg/m3	Fume.

US. ACGIH Threshold Limit Values (TLV)

Additional components	Type	Value	Form
Manganese compounds (potassium permanganate). (CAS 7439-96-5)	TWA	0.1 mg/m3	Inhalable fraction.
		0.02 mg/m3	Respirable fraction.

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Additional components	Type	Value
Manganese compounds (potassium permanganate). (CAS 7439-96-5)	IDLH	500 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Additional components	Type	Value	Form
Manganese compounds (potassium permanganate). (CAS 7439-96-5)	STEL	3 mg/m3	Fume.
	TWA	1 mg/m3	Fume.

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines Follow standard monitoring procedures.

Appropriate engineering controls Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Wear face shield if there is risk of splashes.

Skin protection

Hand protection Wear chemical-resistant, impervious gloves. Use protective gloves made of: Rubber or plastic. Frequent change is advisable. Suitable gloves can be recommended by the glove supplier.

Skin protection

Other Wear appropriate chemical resistant clothing. Rubber or plastic apron. Use of an impervious apron is recommended.

Respiratory protection In case of inadequate ventilation or risk of inhalation of dust, use suitable respiratory equipment with particle filter. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134.

Measurement Element: Manganese (Mn)
10 mg/m3
Any particulate respirator equipped with an N95, R95, or P95 filter (including N95, R95, and P95 filtering facepieces) except quarter-mask respirators. The following filters may also be used: N99, R99, P99, N100, R100 or P100. Any supplied-air respirator.

25 mg/m3
Any supplied-air respirator operated in a continuous-flow mode.
Any powered, air-purifying respirator with a high-efficiency particulate filter.

50 mg/m3
Any air-purifying, full-face piece respirator equipped with an N100, R100, or P100 filter.
Any supplied-air respirator with a tight-fitting face piece that is operated in a continuous-flow mode.
Any powered, air-purifying respirator with a tight-fitting face piece and a high-efficiency particulate filter.
Any supplied-air respirator with a full face piece.

500 mg/m3
Any supplied-air respirator operated in a pressure-demand or other positive-pressure mode.

Emergency or planned entry into unknown concentrations or IDLH conditions -
Any self-contained breathing apparatus that has a full face piece and is operated in a pressure-demand or other positive-pressure mode.

Escape
Any air-purifying, full-face piece respirator equipped with an N100, R100, or P100 filter.
Any appropriate escape-type, self-contained breathing apparatus.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations Keep from contact with clothing and other combustible materials. Remove and wash contaminated clothing promptly. When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Dark purple solid with metallic luster.
Physical state	Solid.
Form	Solid.
Color	Dark purple.
Odor	Odorless.
Odor threshold	Not applicable.
pH	10 (5% solution)
Melting point/freezing point	Starts to decompose with evolution of oxygen (O2) at temperatures above 150 °C. Once initiated, the decomposition is exothermic and self sustaining.
Initial boiling point and boiling range	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	Non flammable.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not applicable.
Explosive limit - upper (%)	Not applicable.
Vapor pressure	Not applicable.
Vapor density	Not applicable.
Relative density	2.7 (20 °C) (Water = 1)
Solubility(ies)	
Solubility (water)	6.4 % (20 °C) (Moderately soluble)
Partition coefficient (n-octanol/water)	Not applicable for norganics.
Auto-ignition temperature	Not available.
Decomposition temperature	464 °F (240 °C)
Viscosity	Not applicable.
Other information	
Bulk density	2.7 g/cm3
Explosive properties	Not explosive. Can explode in contact with sulfuric acid, peroxides and metal powders.
Molecular formula	KMnO4
Molecular weight	158.03 g/mol
Oxidizing properties	May intensify fire; oxidizer. Strong oxidizing agent.

10. Stability and reactivity

Reactivity	Greatly increases the burning rate of combustible materials.
Chemical stability	Stable at normal conditions.
Possibility of hazardous reactions	Contact with combustible material may cause fire. Can explode in contact with sulfuric acid, peroxides and metal powders. Starts to decompose with evolution of oxygen (O2) at temperatures above 150 °C. Once initiated, the decomposition is exothermic and self sustaining.
Conditions to avoid	Contact with incompatible materials or heat (135 °C / 275 °F) could result in violent exothermic chemical reaction.
Incompatible materials	Acids. Alcohols. Peroxides. Reducing agents. Combustible material. Hydrogen fluoride. Metal powders. Contact with hydrochloric acid liberates chlorine gas.
Hazardous decomposition products	Potassium oxides. Manganese oxides. Formic acid.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause irritation to the respiratory system. Prolonged inhalation may be harmful.
Skin contact	Causes severe skin burns. May be harmful in contact with skin.
Eye contact	Causes serious eye damage.

Ingestion Harmful if swallowed. Causes digestive tract burns.

Symptoms related to the physical, chemical and toxicological characteristics Contact with this material will cause burns to the skin, eyes and mucous membranes. Permanent eye damage including blindness could result.

Information on toxicological effects

Acute toxicity Harmful if swallowed.

Product	Species	Test Results
Potassium permanganate (CAS 7722-64-7)		
Acute		
Dermal		
LD50	Rat	2000 mg/kg, 24 Hours
Oral		
LD50	Rat	2000 mg/kg

Additional components	Species	Test Results
Manganese compounds (potassium permanganate). (CAS 7439-96-5)		
Acute		
Oral		
LD50	Rat	9000 mg/kg

Skin corrosion/irritation Causes severe skin burns.

Serious eye damage/eye irritation Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not classified.

Skin sensitization Not classified.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicity Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure May cause damage to organs (Brain) through prolonged or repeated exposure by inhalation.

Aspiration hazard Not likely, due to the form of the product.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure, usually over many years, to manganese oxide fume/dust can lead to chronic manganese poisoning, chiefly affecting the central nervous system.

12. Ecological information

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Product		Species	Test Results
Potassium permanganate (CAS 7722-64-7)			
Aquatic			
Algae	EbC50	Algae	0.43 mg/l, 72 hours
	NOECb	Algae	0.22 mg/l
Crustacea	EC50	Daphnia magna	0.06 mg/l
Fish	EC50	Poecilia reticulata	0.47 mg/l, hours

Persistence and degradability	Expected to be readily converted by oxidizable materials to insoluble manganese oxide.
Bioaccumulative potential	Potential to bioaccumulate is low.
Mobility in soil	The product is miscible with water. May spread in water systems.
Other adverse effects	This product contains one or more substances which may be hazardous air pollutants (HAPs).

13. Disposal considerations

Disposal instructions	Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose of in accordance with local regulations.
Hazardous waste code	D001: Ignitable waste The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Do not allow this material to drain into sewers/water supplies. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Rinse container at least three times to an absence of pink color before disposing.

14. Transport information

DOT

UN number	UN1490
UN proper shipping name	Potassium permanganate
Transport hazard class(es)	
Class	5.1
Subsidiary risk	-
Label(s)	5.1
Packing group	II
Environmental hazards	
Marine pollutant	Yes
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	IB8, IP2, IP4, T3, TP33
Packaging exceptions	152
Packaging non bulk	212
Packaging bulk	240

IATA

UN number	UN1490
UN proper shipping name	Potassium permanganate
Transport hazard class(es)	
Class	5.1
Subsidiary risk	-
Packing group	II
Environmental hazards	Yes
ERG Code	5L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number	UN1490
UN proper shipping name	POTASSIUM PERMANGANATE
Transport hazard class(es)	
Class	5.1
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	Yes
EmS	F-H, S-Q
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
General information	IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

All components are on the U.S. EPA TSCA Inventory List.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. Drug Enforcement Administration (DEA) (21 CFR 1310.02 (b) 8: List II chemical.

Department of Homeland Security (DHS) Chemical Facility Anti-Terrorism Standards (6 CFR 27, Appendix A): Listed.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Potassium permanganate (CAS 7722-64-7) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA) This substance is on the TSCA 8(b) inventory and is designated “active”.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories

Oxidizer (liquid, solid, or gas)
Acute toxicity (any route of exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Potassium permanganate	7722-64-7	>97

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Potassium permanganate (CAS 7722-64-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Clean Water Act (CWA) Section 112(r) (40 CFR 68.130) Hazardous substance

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Potassium permanganate (CAS 7722-64-7) 6579

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Potassium permanganate (CAS 7722-64-7) 15 %WT

DEA Exempt Chemical Mixtures Code Number

Potassium permanganate (CAS 7722-64-7) 6579

US state regulations California OSH Hazardous Substance List: Listed.

US. Massachusetts RTK - Substance List

Potassium permanganate (CAS 7722-64-7)

US. New Jersey Worker and Community Right-to-Know Act

Potassium permanganate (CAS 7722-64-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Potassium permanganate (CAS 7722-64-7)

US. Rhode Island RTK

Potassium permanganate (CAS 7722-64-7)

California Proposition 65

WARNING: This product can expose you to chemicals including Chromates, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 27-November-2013

Revision date 18-July-2023

Version # 07

HMIS® ratings

Health: 3*
Flammability: 0
Physical hazard: 1

NFPA ratings

List of abbreviations

GHS: Globally Harmonized System of Classification and Labeling of hazardous properties of Chemicals.
TWA: Time weighted average.
LD50: Lethal Dose, 50%.
LC50: Lethal Concentration, 50%.
IMDG: International Maritime Dangerous Goods.
IATA: International Air Transport Association.
MARPOL: International Convention for the Prevention of Pollution from Ships.

EC50: Effective Concentration, 50%.
EbC50: EC50 in terms of reduction of biomassNOEC: No Observed Effect Concentration.

References

Chemical safety report. HSDB® - Hazardous Substances Data Bank
Registry of Toxic Effects of Chemical Substances (RTECS)
IARC Monographs. Overall Evaluation of Carcinogenicity
National Toxicology Program (NTP) Report on Carcinogens
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer	The information contained herein is accurate to the best of our knowledge. However, data, safety standards and government regulations are subject to change and, therefore, holders and users should satisfy themselves that they are aware of all current data and regulations relevant to their particular use of product. CARUS LLC DISCLAIMS ALL LIABILITY FOR RELIANCE ON THE COMPLETENESS OR ACCURACY OR THE INFORMATION INCLUDED HEREIN. CARUS LLC MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTIES OF MERCHANTIABILITY OR FITNESS FOR PARTICULAR USE OR PURPOSE OF THE PRODUCT DESCRIBED HEREIN. All conditions relating to storage, handling, and use of the product are beyond the control of Carus LLC, and shall be the sole responsibility of the holder or user of the product. (Carus and design) is a registered service mark of Carus LLC. CAIROX® is a registered trademark of Carus LLC.
This SDS contains revisions in the following section(s):	This safety data sheet contains revisions in the following section(s):